

## High Voltage Fuses VvPa Types

### Високоволтови предпазители тип ВВПа

#### General information

Type: VvPa French Standard  
 Class: HV back-up  
 Standard: UTE C64-210 / IEC 60282-1  
 Pin strike: Yes  
 Application: indoor/outdoor



Rated voltage Ном. напряжение	Rated current Ном. ток	Order № Каталожен №	Length Дължина	Diameter Диаметър	Breaking capacity Изкл. възможност	Weight Тегло
kV	A		L, mm	D, mm	I1, kA	kg.
12	6.3	1310006	259	55	40	1.4
	10	1310010	259	55	40	1.4
	16	1310016	259	55	40	1.4
	20	1310020	259	55	40	1.4
	25	1310025	259	55	40	1.4
	32	1310032	259	55	40	1.4
	40	1310040	259	55	40	1.4
	50	1310050	259	55	40	1.4
24	64	1310064	259	55	40	1.4
	2	1320002	520	55	40	2.7
	4	1320004	520	55	40	2.7
	6.3	1320006	520	55	40	2.7
	10	1320010	520	55	40	2.7
	16	1320016	520	55	40	2.7
	20	1320020	520	55	40	2.7
	25	1320025	520	55	40	2.7
36	32	1320032	520	55	40	2.7
	40	1320040	520	55	40	2.7
	50	1320050	520	55	40	2.7
	64	1320064	520	55	40	2.7
	2	1335002	585	54	20	3.0
	4	1335004	585	54	20	3.0
	6.3	1335006	585	54	20	3.0
	10	1335010	585	54	20	3.0
40	16	1335016	585	54	20	3.0
	20	1335020	585	54	20	3.0
	25	1335025	585	54	20	3.0
	32	1335032	585	54	20	3.0
	40	1335040	585	54	20	3.0

#### General information

Type: VvPb British Standard  
 Class: HV back up  
 Standard: BS 2692-1, IEC 60282-1  
 Pin strike: Yes  
 Application: indoor/outdoor



## High Voltage Fuses VvPb Types

### Високоволтови предпазители тип ВВПб

Rated voltage Ном. напряжение	Rated current Ном. ток	Order № Каталожен №	Length Дължина	Diameter Диаметър	Breaking capacity Изкл. възможност	Weight Тегло
kV	A		L, mm	D, mm	I1, kA	kg.
12	6.3	1410006	254	63.5	40	1.9
	10	1410010	254	63.5	40	1.9
	16	1410016	254	63.5	40	1.9
	20	1410020	254	63.5	40	1.9
	25	1410025	254	63.5	40	1.9
	31.5	1410032	254	63.5	40	1.9
	40	1410040	254	63.5	40	1.9
	50	1410050	254	63.5	40	1.9
24	63	1410063	254	63.5	40	1.9
	80	1410080	254	63.5	40	1.9
	90	1410090	254	63.5	40	1.9
	6.3	1420006	565	50.8	25	2.5
	10	1420010	565	50.8	25	2.5
	16	1420016	565	50.8	25	2.5
	20	1420020	565	50.8	25	2.5
	25	1420025	565	50.8	25	2.5
36	31.5	1420032	565	50.8	25	2.5
	6.3	1435006	565	50.8	25	2.5
	10	1435010	565	50.8	25	2.5
	16	1435016	565	50.8	25	2.5
	20	1435020	565	50.8	25	2.5
	25	1435025	565	50.8	25	2.5
	31.5	1435032	565	50.8	25	2.5